


# LLM Routers

Architecture, Governance, Dynamic Routing,  
Multi-Agent Systems and Security in  
Heterogeneous LLM Ecosystems

---

Aridio Silva · Independent Researcher · ORCID 0009-0008-2411-6995



# Abstract

- LLM routers decide, for each request, which model answers, and add gateway functions: authentication, budgets, fallback, caching and auditing.
- We cover formalization, strategies, API integration, multi-agent systems, GRC, security, benchmarks and maturity.
- Technical review with source auditing: arXiv, ACL, NIST, EUR-Lex and official documentation.

**2×+**

cost savings with quality kept (RouteLLM)

**13.4%**

of calls to GPT-4 recover 50% of performance (RouteLLM)

**−24.7%**

commercial router below the best single model (LLMRouterBench)

# Contents

- 1 Introduction
- 2 Theoretical foundations
- 3 Methodology
- 4 Routing strategies
- 5 Architecture and OpenAI API
- 6 Products
- 7 Models
- 8 Authentication
- 9 Agents and swarms
- 10 Governance, Risk and Compliance
- 11 Threats and vulnerabilities
- 12 Evidence and benchmarks
- 13 Historical evolution
- 14 Maturity and deployment
- 15 Discussion and recommendations
- 16 Conclusion

# A heterogeneous ecosystem calls for a router

## Context

Proprietary, open and reasoning models differ in cost, latency, context and capability.

## Problem

Always using the strongest model is expensive; always using the weakest fails on hard queries.

## Question


How to decide, for each request, which model to use while controlling cost, risk and compliance?

**US\$ 1.25 × US\$ 75**

per million output tokens: Claude 3 Haiku × Claude 3 Opus, 2024 prices

## Figure 1. Conceptual decision flow of an LLM router

From request to response: prompt analysis, policy, routing algorithm, dispatch and validation



*Goal: the smallest model able to solve each request with quality.*

Source: prepared by the author from Ong et al. (2025), Chen et al. (2023), Aggarwal et al. (2024)

© Aridio Silva @aridiosilva — Outubro 2026

# The trilemma: cost, latency and quality

## Cost

Reasoning and large models cost far more per token.

## Latency

Larger models take longer to the first token (TTFT).

## Quality

Smaller models fail on reasoning, code and nuanced analysis.

## Resilience

Providers go down and impose limits (RPM, TPM); the router fails over.

## Principle

**Allocate each request to the smallest model able to solve it with satisfactory quality.**

# Measuring a router: PGR, APGR and CPT

## Threshold routing $\alpha$

Weak model if  $P(\text{strong wins} \mid \text{query}) < \alpha$ ;  
otherwise, strong model.

## PGR

$(r_{\text{router}} - r_{\text{weak}}) / (r_{\text{strong}} - r_{\text{weak}})$ :  
fraction of the performance gap recovered.

## APGR

Mean PGR as  $\alpha$  varies: area under the PGR  $\times$  cost curve.

## CPT(x%)

Smallest fraction of strong-model calls needed to reach a PGR of x%.

*A router that always calls the strong model has PGR = 1 and no savings; hence APGR and CPT.*

# Five ideas that justify routers

**1 No model is best at everything.** Cost, latency and specialty vary.

**2 Queries vary in difficulty.** Many are simple.

**3 Cost is asymmetric.** From 60× to about 100× between models.

**4 The decision can be predicted before generating.** One call per query.

**5 Decouple app and model.** Creates a single control point.

# Seven objectives and how to measure them

| Objective       | How the router pursues it        | KPI                          |
|-----------------|----------------------------------|------------------------------|
| Cost efficiency | Simple queries to cheap models   | Share of strong-model calls  |
| Quality         | Strong model only where required | PGR, APGR, CPT               |
| Low latency     | Smaller models, less reasoning   | TTFT, total latency          |
| Resilience      | Fallback, circuit breaker        | Error rate, availability     |
| Portability     | Single OpenAI-format API         | Time to switch model         |
| Governance      | Virtual keys, budgets, auditing  | Control coverage             |
| Observability   | Central log of cost and model    | Cost per team, agent and app |

# Design principles and costs to consider

## Principles

- Smallest sufficient model
- One call per query
- Tunable trade-off (threshold  $\alpha$ )
- Compare with a simple baseline
- Fail safely (fallback)

## Costs and limits

- Overhead and extra calls in cascades
- Uncertain gain from the algorithm
- New point of failure and attack
- Continuous gateway operation

# Technical review with source auditing

1

## Initial survey

Exploratory research that scoped the topics.

2

## Primary sources

Papers, repositories, documentation, NVD and standards.

3

## Complementing

New papers, OWASP, regulatory milestones and CVEs.

4


## Correction and marking

Errors corrected; what lacks a source is flagged.

Audited source: title, authorship, date, venue and data checked on the page itself; link accessible between 28 and 29 Oct 2026.

# Figure 2. Taxonomy of LLM routing strategies

Predictive routing decides before generating (1 call per query); non-predictive generates, evaluates and escalates ( $\geq 1$  call)



Source: Hu et al. (2024); Ong et al. (2025); Ding et al. (2024); Chen et al. (2023)

© Aridio Silva @aridiosilva — Outubro 2026

## Six strategies, six trade-offs

| Strategy                              | Calls  | Strength                   | Limitation                |
|---------------------------------------|--------|----------------------------|---------------------------|
| Rules                                 | 1      | Transparent and auditable  | Fragile to paraphrases    |
| Preference (SW, MF, BERT, causal LLM) | 1      | Over 2× savings            | Recalibrate the threshold |
| Semantic k-NN                         | 1      | Simple and incremental     | Depends on labeled base   |
| Cascade                               | 1 to N | Up to 98% savings reported | Accumulated latency       |
| Self-verification + POMDP             | 1 to N | Works with black-box APIs  | Noisy verification        |
| LLM-as-a-Judge                        | 2 to N | Flexible criterion         | Judge cost and bias       |

# RouteLLM: human preferences become a router

## SW ranking

Similarity-weighted Bradley-Terry; no training.

## Matrix Factorization

Bilinear score between model and query embeddings.

**~65,000**

Chatbot Arena comparisons (64 models)

## BERT

Fine-tuned BERT-base with a logistic head.

## Causal LLM

Llama 3 8B predicts the win probability.

**~120,000**


GPT-4 judge labels

**US\$ 700**

approximate cost of the labels

# Figure 3. Reference architecture of an LLM Router / AI Gateway

Control plane between clients and providers, exposed through an OpenAI-compatible API (POST /v1/chat/completions)



© Aridio Silva @aridiosilva — Outubro 2026

# The OpenAI standard: the request

```
curl http://localhost:4000/v1/chat/completions \
-H "Authorization: Bearer $KEY" \
-H "Content-Type: application/json" \
-d '{
  "model": "auto-router-cost-saving",
  "messages": [
    {"role": "user",
     "content": "Capital of France?"}
  ],
  "stream": false
}'
```

- POST /v1/chat/completions
- Authorization: Bearer <virtual key>
- model: model, alias or policy
- messages: list with role and content
- stream, tools, response\_format...

*Format launched with the ChatGPT API on 1 Mar 2023.*

# The response and streaming

```
{
  "id": "chatcmpl-example-123",
  "object": "chat.completion",
  "model": "openai/gpt-4o-mini",
  "choices": [{
    "index": 0,
    "message": {"role": "assistant",
      "content": "Paris."},
    "finish_reason": "stop"
  }],
  "usage": {"prompt_tokens": 25,
    "completion_tokens": 8,
    "total_tokens": 33}
}
```

- stream: true → SSE events "data: {...}"
- chat.completion.chunk objects, same id
- The stream ends with data: [DONE]
- include\_usage: usage in the last chunk
- The model field is the model actually used

*Illustrative example; invented values.*

## Open-source and managed: the ecosystem

| Solution   | Delivery                   | Highlight                                        |
|------------|----------------------------|--------------------------------------------------|
| LiteLLM    | Open-source, self-hosted   | 100+ providers, virtual keys, spend control      |
| RouteLLM   | Open-source (Apache-2.0)   | Trained routers, threshold calibration           |
| LLMRouter  | Open-source (research)     | 16+ routers in one interface                     |
| OpenRouter | SaaS                       | One key; fallback via the models field           |
| Portkey    | SaaS, open core            | Fallback, cache, conditional routing, guardrails |
| Helicone   | Open-source, observability | Cache, rate limits, cost alerts                  |

# Models: what can be stated with a source

60×

Claude 3 Haiku × Opus: US\$ 1.25 × US\$ 75 per million tokens (2024)

~100×

Mixtral-8x7B × GPT-4: US\$ 0.24 × US\$ 24.7 per million tokens

2–5×


cost variation at comparable performance (RouterBench)

| Previous model | GPT-5 model         |
|----------------|---------------------|
| GPT-4o         | gpt-5-main          |
| GPT-4o-mini    | gpt-5-main-mini     |
| OpenAI o3      | gpt-5-thinking      |
| OpenAI o4-mini | gpt-5-thinking-mini |
| GPT-4.1-nano   | gpt-5-thinking-nano |
| OpenAI o3 Pro  | gpt-5-thinking-pro  |

Prices and catalogs change: check the official pages.

## Figure 5. Two-layer authentication

The client only knows virtual credentials; the providers' master keys stay in the gateway vault



Source: LiteLLM and OpenRouter documentation (2026)

© Aridio Silva @aridiosilva — Outubro 2026

## Virtual keys: five best practices


- 1 **Least privilege** allowed models per key
- 2 **Short lifetime** and automatic rotation
- 3 **Budgets and limits** per key, team and global
- 4 **Block api\_base** parameters that change the destination
- 5 **Separate the planes** data × control, by network and role

### CVE-2024-6587

The api\_base parameter redirected the call and leaked the OpenAI key.

# Figure 6. Role-based routing in multi-agent systems and swarms

The gateway maps each role to a model and protects the swarm from traffic spikes and provider failures



© Aridio Silva @aridiosilva — Outubro 2026

## Swarms: traffic and cost containment

### Priority queues

The orchestrator goes ahead of background tasks.

### Token bucket

Controls RPM and TPM with backpressure, without breaking agent state.

### Cache with caution


Semantic cache is designed for single-turn use and can err in agentic flows.

### Fallback and budget

Provider switch on failure; budget per agent or run.

## Figure 7. GRC pipeline in the gateway and regulatory mapping

Each request step implements a verifiable control and produces audit evidence



*Each control produces evidence for auditing.*

Source: NIST AI 100-1; NIST AI 600-1; Reg. (EU) 2024/1689; LGPD; OWASP


© Aridio Silva @aridiosilva — Outubro 2026

## Reference frameworks: from NIST to LGPD

| Framework       | Date                | What it brings to the gateway                                                                   |
|-----------------|---------------------|-------------------------------------------------------------------------------------------------|
| NIST AI RMF 1.0 | 26 Jan 2023         | Govern, Map, Measure, Manage                                                                    |
| NIST AI 600-1   | Jul 2024            | Generative AI profile                                                                           |
| ISO/IEC 42001   | Dec 2023            | AI management system                                                                            |
| EU AI Act       | in force 1 Aug 2024 | Event logging (art. 12); high-risk postponed to 2 Dec 2027 (Annex III) and 2 Aug 2028 (Annex I) |
| LGPD            | Law 13,709/2018     | Security (art. 46), international transfer (33), records (37), incidents (48)                   |

## Figure 8. Threat model and attack surfaces of an LLM gateway

Threats organized by trust boundary, referencing the OWASP Top 10 for LLM (2025) and real CVEs



Source: OWASP (2024); NVD; GitLab Advisory Database

© Aridio Silva @aridiosilva — Outubro 2026

# Real vulnerabilities documented in LiteLLM

*Lesson: continuous updates and defense in depth.*

| Class                | Case                                  | Version     |
|----------------------|---------------------------------------|-------------|
| SSRF and key leak    | CVE-2024-6587 (NVD, 13 Sep 2024)      | 1.38.10     |
| RCE                  | Advisory: eval in get_secret()        | 1.35.8      |
| RCE                  | Advisory: configuration handling      | 1.40.12     |
| Leak in logs         | Part of the key exposed in a log file | 2024        |
| Integration secrets  | Langfuse keys leaked                  | 2024-2025   |
| Privilege escalation | internal_user_viewer role             | main-latest |
| SQL injection        | api_key parameter in a SQL query      | 2024        |

# The routing algorithm itself can be attacked

**~100%**

success of confounder gadgets on open routers (worst case: 88%)

**6–31 min**

to generate a gadget (6 min on causal LLM, 31 min on SW)

**>99%**

detection accuracy of RerouteGuard (2026)

**Cost escalation**

Forces the expensive model.

**Quality hijacking**


Forces the weak model on complex queries.

**Safety bypass**

Diverts harmful queries to a weaker model.

## Figure 4. Cost to recover performance on MT Bench (RouteLLM)

CPT(50%) and CPT(80%) points reported by Ong et al. (2025, Table 1); segments between points are illustrative interpolation



### Reading

To recover 50% of the gap between Mixtral and GPT-4, the MF router sends 13.4% of the queries to GPT-4; the random one, 49.0%.

For 80%: 31.3% versus 78.1%.

Source: Ong et al., RouteLLM, ICLR 2025, Table 1.

© Aridio Silva @aridiosilva — Outubro 2026

## RouteLLM on MT Bench: cost to recover performance

| Training data       | Router               | CPT(50%) | CPT(80%) | APGR  |
|---------------------|----------------------|----------|----------|-------|
| —                   | Random               | 49.03%   | 78.08%   | 0.500 |
| Arena               | Matrix Factorization | 25.32%   | 74.26%   | 0.580 |
| Arena               | SW Ranking           | 37.85%   | 58.99%   | 0.610 |
| Arena + GPT-4 judge | BERT                 | 19.58%   | 34.02%   | 0.751 |
| Arena + GPT-4 judge | Causal LLM           | 31.50%   | 48.75%   | 0.679 |
| Arena + GPT-4 judge | Matrix Factorization | 13.40%   | 31.31%   | 0.802 |

*More data matters more than architecture: the best result is MF with augmented data.*

## Three benchmarks, three points of view

| Criterion        | RouterBench                         | RouteLLM                  | LLMRouterBench                       |
|------------------|-------------------------------------|---------------------------|--------------------------------------|
| Scale            | 405k samples, 11 models, 8 datasets | GPT-4 / Mixtral-8x7B pair | 33 models, 21 datasets, ~1.8B tokens |
| Trade-off KPI    | AIQ (NDCH)                          | APGR, CPT                 | PerfGain, CostSave, ParetoDist       |
| Baselines        | Zero router, Oracle                 | Random                    | Random, Best Single, Oracle          |
| Latency          | Not measured                        | Not central               | Approximate analysis                 |
| Model generation | 2023                                | 2023–2024                 | 2025                                 |

## LLMRouterBench: the critical counterpoint

**33 · 21**

models · datasets

**+4%**

maximum gain over the  
Best Single

**−24.7%**

OpenRouter router vs. Best  
Single (GPT-5)


**31.7%**

largest saving without  
losing accuracy

- Most methods converge to similar performance.
- Several do not reliably beat a simple baseline.
- Large gap to the Oracle, due to model-recall failures.
- The embedding model has little impact.

# Figure 9. Evolution of LLM routers by phase (2020-2026)

Scientific, product, security and regulatory milestones of each phase



Source: arXiv, ICLR, NeurIPS, ACL, NVD, OWASP, NIST, EUR-Lex

© Aridio Silva @aridiosilva — Outubro 2026

**5 phases**

2020-22: monolithic era

2023: gateways


2024: benchmarks and CVEs

2025: reasoning and regulation

2026: consolidation and agents

# Figure 10. Timeline by topic lane (2020-2026)

Scientific, product, security and regulatory milestones on a linear time scale



© Aridio Silva @aridiosilva — Outubro 2026

Figure 11. Maturity of LLM routers (Oct 2026)

Author's assessment per dimension, based on the evidence in Section 14 (scale from 1 to 5)

|                         | 1<br>Research | 2<br>Prototype | 3<br>Early adoption | 4<br>Wide production | 5<br>Commodity | Evidence                                |
|-------------------------|---------------|----------------|---------------------|----------------------|----------------|-----------------------------------------|
| Gateway / unified API   |               |                |                     | 4                    |                | LiteLLM, OpenRouter                     |
| Fallback and limits     |               |                |                     | 4                    |                | Native in gateways                      |
| Keys, budget, logs      |               |                |                     | 4                    |                | Native; CVEs require updates            |
| Rule-based routing      |               |                |                     | 4                    |                | Hard-to-beat baseline                   |
| Learned binary          |               |                | 3                   |                      |                | RouteLLM; does not beat the Best Single |
| Learned multi-model     |               | 2              |                     |                      |                | Far from the Oracle                     |
| In mass-market product  |               |                | 3                   |                      |                | GPT-5 (Aug 2025)                        |
| Agentic / multi-turn    |               | 2              |                     |                      |                | Active research                         |
| Latency-aware           | 1             |                |                     |                      |                | Not optimized                           |
| Adversarial robustness  | 1             |                |                     |                      |                | Rerouting up to ~100%                   |
| Standardized evaluation |               |                | 3                   |                      |                | Benchmarks still fragmented             |

Two maturities

Control plane: level 4

Intelligent decision: levels 2–3

Latency and adversarial robustness: level 1

Source: Hu et al. (2024); Ong et al. (2025); Li et al. (2026); Shafran et al. (2025); OpenAI (2025)

© Aridio Silva @aridiosilva — Outubro 2026

## Overhead and throughput: measure in your own environment

| Router               | req/s  | US\$ / million |
|----------------------|--------|----------------|
| SW ranking (CPU)     | 2.9    | 39.26          |
| Matrix Factorization | 155.16 | 3.32           |
| BERT                 | 69.62  | 3.19           |
| Causal LLM           | 42.46  | 5.23           |

*RouteLLM algorithms, measured by the authors.*

*Competitor measurements differ and have a conflict of interest.*

**$\leq 0.4\%$**

maximum router cost over GPT-4 generation

**1,170 req/s**

LiteLLM, 4 instances (official documentation)

**8 ms**

gateway p95 overhead in that test

## Positive and negative implications

### Positive

- Savings of over 2× up to 3.66×
- Automatic fallback across providers
- Single governance point
- Model switching by configuration

### Negative

- Uncertain algorithm gain
- New point of failure and attack
- Extra latency and recalibration
- User may not know which model answered

## Recommendations by scenario

| Scenario                       | Recommendation                                                                           |
|--------------------------------|------------------------------------------------------------------------------------------|
| Production with sensitive data | Self-hosted gateway in a VPC, virtual keys, DLP, auditing and updates against advisories |
| Cut cost at scale              | Start with rules; adopt a learned router only if it beats the baseline on real traffic   |
| Prototypes and startups        | Managed aggregator with fallback; data passes through the vendor                         |
| Multi-agent                    | Model and reasoning per role, queues, token bucket and per-run budget                    |
| Compliance                     | Data residency, event logging and control-requirement mapping                            |

# Conclusion and future work

## Conclusion

- The problem admits precise formalization (PGR, APGR, CPT).
- The control plane is mature; the decision algorithm must prove its gain.
- Latency and adversarial robustness are the gaps.

## Future work

- Joint routing of model and reasoning effort
- Multi-turn and agentic routing with budgets
- Evaluation under attack
- Benchmarks with 2026 models
- Governance metrics

# Main sources

- Ong et al. (2025). RouteLLM. ICLR 2025. arXiv:2406.18665
- Li et al. (2026). LLMRouterBench. Findings of ACL 2026. arXiv:2601.07206
- LLMRouter (2026). arXiv:2608.06867
- Chen, Zaharia, Zou (2023). FrugalGPT. arXiv:2305.05176
- Hu et al. (2024). RouterBench. arXiv:2403.12031
- Ding et al. (2024). Hybrid LLM. ICLR 2024. arXiv:2404.14618
- Aggarwal et al. (2024). AutoMix. NeurIPS 2024. arXiv:2310.12963
- Shafran et al. (2025). Rerouting LLM Routers. arXiv:2501.01818
- RerouteGuard (2026). arXiv:2601.21380

*43 audited references in the full document, between 28 and 29 Oct 2026.*

# Key messages

## Control plane

Gateway, fallback, keys, budgets and auditing are already in wide production.

## Intelligent decision

The algorithm's gain must be proven against a simple baseline.

## Security

The gateway concentrates keys and data; routing itself can be attacked.

Aridio Silva · Independent Researcher · @aridiosilva · ORCID 0009-0008-2411-6995